



## G5500063

### PANEL

Active Display Area	55" (1211.6 x 682.4 mm)
Backlight Resolution	LED
Pixel Pitch (mm)	1920 x 1080
Brightness	0.63 mm (H) x 0.63 mm (V)
Contrast Ratio	2500 cd/m <sup>2</sup> (Typ)
Viewing Angle	5000:1
Display Colours	178° (H) 178° (V) with CR≥10 16.7 Million colours (Max)

### CONNECTIVITY

Video	
Power Consumption (Max)	HDMI, DVI, VGA
Power Input	500 W
External Controls	115 - 230 VAC
Diagnostic	STandard USB or RJ45 Ethernet cable connection Diagnostic parameters managed through SNMP GDS subagent: LCD screen state, internal temperature - humidity level control, vibration sensor, internal heater state, fan state and speed control, ambient light and LCD backlight control

### MECHANICAL STRUCTURE

Dimensions (W-H-D)	842 x 1370 x 169.5 mm
Weight	103 Kg
Wall Mounting	4 Fixing points each side are available for wall mounting
Protective Glass	Monolithic toughened or laminated glass (IK-08 impact resistance) and optical enhancement G+Bond
Self-Standing Mounting	Yes
Operating Temperature	-25°C to +45°C (Full sunlight conditions) -25°C to +50°C (Covered)

### SPECIAL FEATURES

Bezel	70 mm
Special Features	MTBF 50000 hours Book frontal opening
IP Class	IP65

### EMBEDDED PC

Optional upon request

### CERTIFICATION

CE, UL

### ACCESSORIES

Possibility of master and slave versions

